

PIRPORTATION OF CONTRACTOR OF

PIN NO.	CIRCUIT	COLOUR	
1	LEFT- HAND TURN - 4MM	YELLOW	
2	BREAK SAFE = AUX - 4MM	BLACK	
3	EARTH RETURN – 4MM	WHITE	
4	RIGHT-HAND TURN - 4MM	GREEN	
5	ELECTRIC BRAKES - 5MM	BLUE	
6	STOP LAMPS - 4MM	RED	
7	REAR LAMPS, CLEARANCE & SIDE MARKER LAMPS - 4MM	BROWN	
8	SPARE	SPARE	
9	3-WAY FRIDGE ONLY - 10MM	RED	
10	COMMON EARTH - 10MM REQUIRED	BLACK	
11	IGNITION D+ TRIGGER - 6MM (SMART ALTERNATOR ONLY)	RED	
12	BRAKE SAFE MONITOR IN CAR (NSW) - 4MM	PURPLE	

Please note: 50 AMP Vehicle Anderson MUST be wired in a MINIMUM of 13.5mm twin cable to provide adequate supply to DC2DC. Always refer to wiring specifications of braking system before connection of service. Dexter / Tuson ESC powered by house battery.

CHASSIS 'A' FRAME



Your Caravan is equipped with a 50 Amp GREY Anderson Plug on the 'A' frame that has been wired to the DC2DC. FOR VEHICLE – CARAVAN CHARGING ONLY.

GREY

PLUG

ANDERSON



Your Caravan is equipped with a 50 Amp RED Anderson Plug on the 'A' frame that has been wired to the DC2DC. FOR PORTABLE UNREGULATED SOLAR CONNECTION ONLY.



Your Caravan is equipped with a 50 Amp BLUE Anderson Plug on the 'A' Frame that has been wired for constant 12 Volt Power (OUTPUT). FOR THE CONNECTION OF 12VOLT EQUIPMENT – eg – CHEST FRIDGES OR JOCKEYWHEELS.



BREAKAWAY SWITCH

Breakaway Switch Wired to Breaksafe 6000